

STANDARD WHITE LIGHT LOOSELED STRIPS

Code	LED Colour	N. of LEDs (m)	LED distance	Length x width	Input Voltage	A (m)	W (m)	Max. capacity	Emission angle
3200K WHITE LooseLED STRIPS									
AL1106	3200K white	20	50.0 mm	1000x8.70 mm	24 V DC	0.10 A	2.5 W	20 m	120°
AL1107	3200K white	30	33.3 mm	1000x8.70 mm	24 V DC	0.17 A	4.0 W	8 m	120°
AL1108	3200K white	40	25.0 mm	1000x8.70 mm	24 V DC	0.23 A	5.5 W	6 m	120°
AL1109	3200K white	50	20.0 mm	1000x8.70 mm	24 V DC	0.27 A	6.5 W	4 m	120°
AL1110	3200K white	100	10.0 mm	1000x8.70 mm	24 V DC	0.54 A	13.0 W	2 m	120°
4200K WHITE LooseLED STRIPS									
AL1111	4200K white	20	50.0 mm	1000x8.70 mm	24 V DC	0.10 A	2.5 W	20 m	120°
AL1112	4200K white	30	33.3 mm	1000x8.70 mm	24 V DC	0.17 A	4.0 W	8 m	120°
AL1113	4200K white	40	25.0 mm	1000x8.70 mm	24 V DC	0.23 A	5.5 W	6 m	120°
AL1114	4200K white	50	20.0 mm	1000x8.70 mm	24 V DC	0.27 A	6.5 W	4 m	120°
AL1115	4200K white	100	10.0 mm	1000x8.70 mm	24 V DC	0.54 A	13.0 W	2 m	120°
5800K WHITE LooseLED STRIPS									
AL1116	5800K white	20	50.0 mm	1000x8.70 mm	24 V DC	0.10 A	2.5 W	20 m	120°
AL1117	5800K white	30	33.3 mm	1000x8.70 mm	24 V DC	0.17 A	4.0 W	8 m	120°
AL1118	5800K white	40	25.0 mm	1000x8.70 mm	24 V DC	0.23 A	5.5 W	6 m	120°
AL1119	5800K white	50	20.0 mm	1000x8.70 mm	24 V DC	0.27 A	6.5 W	4 m	120°
AL1120	5800K white	100	10.0 mm	1000x8.70 mm	24 V DC	0.54 A	13.0 W	2 m	120°